

Rack mural 19" 12U F-600mm. IP55

Ref.: 691712IP55.2



General data

Steel sheet housing with welded corpus, completely pre-assembled
Right- and left-sided metal covered air inlets for passive ventilation
Side walls not detachable

Roof hinged, inner roof prepared for mounting of Plug&Play fan unit Art.-No. 691656GR (cable not included, please order separately, e.g. Art.-No. EK504.x)

Bottom with PG glands 1 x PG48, 2 x PG21 and 3 x Ø 20 mm PVC blind grommets

For depth 450 mm inside 2 x 19" profile rails front-sided, galvanised, with numbering of rack units (U)

For depth 600 mm inside 4 x 19" profile rails (2 front, 2 rear), galvanised, with numbering of rack units (U)

Front door steel sheet with reinforcement and 3-point bar locking, lockable, with profile half-cylinder acc. to DIN 18252 / EN1303

Profile half-cylinder exchangeable by customer

Cabinet parts inside completely earthed

Max. load 100 kg

Paint finish RAL7035, light grey

Protection degree IP55

Plinth for use as standing cabinet available as option

Included accessories: 4 x Wall mount angle, 2 x key

Rack mural 19" 12U

F-600mm. IP55

Allgemeine Daten	
Modular spacing	482.6 mm (19 inch)
With front door	True
Type of ventilation	Passive
Demountable	True
Surface finishing	powder coating
Number of cartons	1
With roof plate	True
Degree of protection (IP)	IP55
With sidewall	True
Mounting level	Front and rear
Model	With permanent frame
With earthing	True
Number of doors	1
Material	steel
Type of profile rail	L-shaped