

Cable telefónico plano 10 vías negro



General data

According German Post Office standard

1=white, 2=brown, 3=green, 4=yellow, 5=grey, 6=pink, 7=blue, 8=red, 9=black, 10=violett

Unshielded

Allgemeine Daten

Conductor category	Class 2 = stranded
Armouring	False
Longitudinal water blocking	False
Material outer sheath	Polyvinyl chloride (PVC)
Outdoor use permitted	False
Core identification	Colour
Circuit integrity	False
Radial water blocking	False

Kabelaufbau

Diameter conductor	0.33 mm
--------------------	---------

Kabelmantel

Flame retardant	False
Protective sheath	False

Umgebungsbedingungen

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.

Cable telefónico plano 10 vías negro

Permitted cable outer temperature during assembling/handling	60 - °C
Permitted cable outer temperature after assembling without vibration	60 - °C

Elektrische Eigenschaften

Core insulation	Polypropylene (PP)
Screen over stranding	None
Screen over stranding element	None

Normen, Zulassungen, Zertifizierungen

Low smoke (according to EN 61034-2)	False
Halogen free (acc. EN 50267-2-2)	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Number of cores	Außendurchmesser ca.
91104.100	Modular Flat Cable, 4-pole black, 100 m reel	black	4	2,5 x 5,0 mm
91104.500	Modular Flat Cable, 4-pole black, 500 m reel	black	4	2,5 x 5,0 mm
91105.100	Modular Flat Cable 4-pole light grey, 100 m reel	grey	4	2,5 x 5,0 mm
91106.100	Modular Flat Cable, 6-pole black, 100 m reel	black	6	2,5 x 7,0 mm
91106.500	Modular Flat Cable, 6-pole black, 500 m reel	black	6	2,5 x 7,0 mm
91107.100	Modular Flat Cable 6-pole light grey, 100 m reel	grey	6	2,5 x 7,0 mm
91108.100	Modular Flat Cable, 8-pole black, 100 m reel	black	8	2,5 x 8,8 mm
91108.500	Modular Flat Cable, 8-pole black, 500 m reel	black	8	2,5 x 8,8 mm
91109.100	Modular Flat Cable 8-pole light grey, 100 m reel	grey	8	2,5 x 8,8 mm
91110.100	Modular Flat Cable, 10-pole black, 100 m reel	black	10	2,5 x 10,7 mm

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.