



Descripción

The ECOLAN® RJ45 plug provides a combination of excellent transmission quality and fast and easy tool-free assembly. IDC terminals and very low contact resistances assure high quality contacting for installation cables up to 9mm diameter and wire gauge from AWG22 - AWG27.

Unshielded polycarbonate body with separate dust cap and anti-kink sleeve
 Cat.6/Class E performance according to ISO/IEC11801 and IEC60603-7-4
 Compact cable manager for AWG 22/1 .. AWG 26/1 or AWG22/7 .. AWG27/7
 Pair management according to TIA 568A /B colour codes and industrial Profinet 1-2-3-6
 Re-termination capability up to 5 times with the same width, for AWG27/7 up to 2 times
 Suitable for cable dia from 6,0mm .. 9,0mm
 Strain relief with cable tie

%BUPT (FOFSBMFT

Category	6
Model	jack (jack)
Connection type	LSA
Type of connector	RJ45 8(8)
Screened	False
AWG-range for solid core	22 27
Special tool necessary	False
Suitable for round cable	True
Suitable for flat cable	False
Suitable for litz wire conductor	True
Suitable for solid core	True

Available variants

Article no.	Title	Colour
E h	Z: hdW	black

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.