

Conector RJ49 Cat.6 TM21 Hirose+protector gris+guía



General data

Channel Class E up to 250 MHz (Cat.6)
 For stranded wires (AWG 24/7, AWG 26/7, AWG 27/7)
 Shielded version
 Core insulation about 0.9 - 1.0 mm
 Cable diameter max. 6.6 mm
 The set consists of RJ plug, anti-kink sleeve and guide plate
 Suitable crimping tool DCW1002 + DCW1002.1 or 39934.2

Allgemeine Daten

Connection type	crimp
Type of connector	RJ45 8(8)
AWG-range	24 - 26
Suitable for litz wire conductor	True
Special tool necessary	True
Suitable for solid core	False
AWG-range for litz wire conductor	24 - 27
Suitable for flat cable	False
Suitable for round cable	True
Category	6
Model	plug

Elektrische Eigenschaften

screened	True
----------	------

Available variants

ArtNr.	Bezeichnung	Colour
H7641.12-1	RJ45-Hirose Connector TM21 grey , 1 pcs., 3 Elements, Cat.6	grey
H7641.12-10	RJ45-Hirose Connector TM21 grey 10 pcs., 3 Elements, Cat. 6	grey
H7641.12-50	RJ45-Hirose Connector TM21 grey 50 pcs., 3 Elements, Cat. 6	grey
H7641.12-100	RJ45-Hirose Connector TM21 grey 100 pcs., 3 Elements, Cat. 6	grey

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.