

# LATIGUILLO CAT. 5E FTP PVC



## TECHNICAL PARAMETERS

1 Gigabit Ethernet Cat.5e 100 MHz patch cable  
2 x RJ45 plug shielded, IEC 60603-7-3  
F/UTP 4 x 2 x AWG26/7 PVC Ø=5.6 mm, foil shielded  
TIA/EIA 568B coded, flame retardant IEC 60332-1  
Moulded strain relief boot with latch protection

<b>Category:</b>	5E
<b>Cable type:</b>	F/UTP
<b>Type of connector connection 1:</b>	RJ45 8(8)
<b>Type of connector connection 2:</b>	RJ45 8(8)
<b>Colour outer sheath:</b>	grey
<b>Anti-kink sleeve:</b>	plugged in
<b>Locking lever:</b>	True
<b>Colour anti-kink sleeve:</b>	grey
<b>Flame retardant version:</b>	False
<b>Halogen free:</b>	False
<b>Oil resistant (acc. EN 60811-2-1):</b>	False
<b>Cable construction:</b>	4x2
<b>NVP value:</b>	- %
<b>Pin assignment:</b>	1:1
<b>AWG-size:</b>	26

*Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.*