




REV	ZONE	REVISION	DATE	MODIFY



Specification

- 1>Contact Resistance 35 m Ohm Max.
- 2 Insulation Resistance 200 M Ohm Min. At 500V DC.
- 3>Contact Current Rating 1 Amp AC/DC
- 3 Voltage Rating 40V AC
- 4 Withstanding Voltage 500V AC For 1 Minute.
- 5 Operating Temperature -25°C to +85°C
- 6 Packing Tray
- 7 Control Dimensions Indicated From ▲ ↑

Material and Finish

- 1 Insulator Material: PBTUL94-V0,Black
- 2 Cover Material: PBTUL94-V0,Black
- 3 Hood Plastic Material: ABS,Black
- 4 Bullon Plastic Material: ABS,Black
- 5 Contact Material: Phosphor Bronze(C319)-DDT+0.25
- 6 Contact Area Plated Gold 1-30u' Plated Over Nickel 50u'.
- 7 Solder Area Plated Tin Plated(80u' min Lead Free)
- 8 Up or Down Shell Material: SPCC T=0.50
- 9 Up or Down Shell Plated Nickel 80u' Plated Over Cu 50u'
- 10 Connector Shell Material: SPCC T=0.50
- 11 Connector Shell Plated Gold 1-3u' Plated Over Cu 50u'
- 12 Hook Spring Material: Stainless Steel T=0.30

