

DATASHEET

Cat.6 Class E 24-Port Patchpanel STP 250MHz 19" 1U, RAL7035



High-Shielded Class E 250MHz patchpanel according to ISO/IEC 11801 and EN50173 for the use in structured cabling systems. Wire connection over LSA-terminal AWG22-AWG24. With sheath clamp for earthing. Strain relief via cable tie.

Mounting method:	482.6 mm (19 inch)-installation
Category:	6
Number of height units:	1
Connection type:	LSA
Type of connector:	RJ45 8(8)
Screened:	True
Height:	44.5 mm
Width:	483.0 mm
Depth:	142.8 mm

Article no.	Title	Number of buses/couplings	Colour	RAL-number
PA37667	Patchpanel 24xRJ45 Cat.6 / Class E, 1U, RAL7035 grey	24	grey	7035
PA37667SW	Patchpanel 24xRJ45 Cat.6 / Class E, 1U, RAL9005 black	24	black	9005
PA37687	Patchpanel 48xRJ45 Cat.6 / Class E, 1U, RAL7035 grey	48	grey	7035
PA37687SW	Patchpanel 48xRJ45 Cat.6 / Class E, 1U, RAL9005 black	48	black	9005

**Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.*