

FTTH IP65 Connectionbox for 8fiber, 4 adapter and Fiber overlength box



General data

Application:

Optical Telecommunication Networks
LAN, Optical fiber Communication Network
CATV Networks
FTTH access Network
PON, G-PON

Configuration in LC with duplex adapters for 8 ports/ fibers

Configuration in SC with simplex adapters for 4 ports/ fibers



Ideal Technology tiene una política de mejora continua. Las especificaciones están sujetas a cambios sin previo aviso.

FTTH IP65 Connectionbox for 8fiber, 4 adapter and Fiber overlength box



Delivery unassembled (**Crimp splice holder (12 splices)**), shrink splice holder (max. 8 splices double layed), 4x shrink protection and material for wall mounting included)

Allgemeine Daten	
Holder for splitter	False
Colour	white
Max. Assembly (Adapter)	4
With Fiber overlength cassette	True
Cable sheath support	True
Hinged splice cassette	True
Suitable for adapter	SC Simplex/LC Duplex/E2000®
Cable entry without cable gland	1x max. 10mm / 4x max. 4mm
Scope of application	Outdoor
Mounting method	Wall mounting
Holder for gas blocker	False
Type of Splice protection	Crimp & Thermo
Possibility of mast mounting	False
Number of Fibres	8

Mechanische Eigenschaften	
IP Protection	IP65
Water protection	Protection against jet water
Foreign body and contact protection	Protection against ingrees of dust

Abmessungen	
Dimension	172x136x40 mm

Umgebungsbedingungen	
Temperature range	-25 - 70 °C

Available variants		
ArtNr.	Bezeichnung	Access Control
CAE8	FTTH IP65 Connectionbox for 8fiber, 4adapter and Fiber overlength box	Special screw/ Seal



Ideal Technology tiene una política de mejora continua. Las especificaciones están sujetas a cambios sin previo aviso.