Conector RJ49 Cat.6 TM21 Hirose+protector





Description

Channel Class E up to 250 MHz (Cat.6) For stranded wires (AWG 24/7, AWG 26/7, AWG 27/7) Shielded version Core insulation about 0.9 - 1.0 mm Cable diameter max. 6.6 mm The set consists of RJ plug, anti-kink sleeve and guide plate Suitable crimping tool DCW1002 + DCW1002.1 or 39934.2

General data

General data		
Category	6	
Model	jack (jack)	
Connection type	crimp	
Type of connector	RJ49 8(8)	
Screened	True	
AWG-range for litz wire conductor	24 - 27	
AWG-range for solid core	24 – 26	
Special tool necessary	True	
Suitable for round cable	True	
Suitable for flat cable	False	
Suitable for litz wire conductor	True	
Suitable for solid core	False	

Available variants		
Article no.	Title	Colour
H7641.1-100	RJ49-Hirose Connector TM21 beige 100pcs, Cat. 6	BEIGE
H76414100	RJ49-Hirose Connector TM21 black 100pcs, Cat. 6	BLACK
H7641.6-1000	RJ49-Hirose Connector TM21 red 100 pcs, Cat. 6	RED

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.

. . . .