

# DATASHEET

Connection Wire YV, Cores x Ø Conductor  
2 x 0.5 / 0.9 mm

Article no.

HP205BZ



## Description

Other types on request

## General data

Longitudinal water blocking	False
Radial water blocking	False
Outdoor use permitted	False
Circuit integrity	No

## Kabelaufbau

Conductor category	Kl.1 = single wire
Diameter conductor	0.5 mm
Number of stranding elements	2
Stranding	-
Stranding element	Pairs
Core insulation	PVC
Core identification	Colour
Screen over stranding element	without
Screen over stranding	without
Armouring	False

## Kabelmantel

Protective sheath	No
Material outer sheath	-
Halogen free (acc. EN 50267-2-2)	False
Flame retardant	according to EN 60332-1-2
Low smoke (acc. EN 61034-2)	False

This datasheet was created automatically on 07-04-2019 . Technical changes reserved.

# DATASHEET

Connection Wire YV, Cores x Ø Conductor  
2 x 0.5 / 0.9 mm

Article no.

HP205BZ

## Environmental conditions

Operating temperature, flexible	70 - °C
Operating temperature, fix	70 - °C

## Available variants

Article no.	Title	Outer diameter approx.	Colour outer sheath	Number of cores
HP205BM	YV 2 x 0.5/0.9 white-brown, Ring 100 m	0.9 mm	white/brown	2
HP205RZ	YV 2 x 0.5/0.9 red-blue, Ring 100 m	0.9 mm	red/blue	2
HP205BV	YV 2 x 0.5/0.9 white-green, Ring 100 m	0.9 mm	white/green	2
HP205BA	YV 2 x 0.5/0.9 white-yellow, Ring 100 m	0.9 mm	white/yellow	2
HP205BZ	YV 2 x 0.5/0.9 white-blue, Ring 100 m	0.9 mm	white/blue	2
HP205BR	YV 2 x 0.5/0.9 white-red, Ring 100 m	0.9 mm	white/red	2
HP205BN	YV 2 x 0.5/0.9 white-black, Ring 100 m	0.9 mm	white/black	2
HP205BP	YV 2 x 0.5/0.9 white-pink, Ring 100 m	0.9 mm	white/pink	2
HP205NR	YV 2 x 0.5/0.9 black-red, Ring 100 m	0.9 mm	black/red	2
HP205RV	YV 2 x 0.5/0.9 red-green, Ring 100 m	0.9 mm	red/green	2