

CABLE HDMI TIPO A M/M CON FERRITA



TECHNICAL PARAMETERS

Shielding: foil + braiding + PIMF
Conductor: bare copper, Jacket: PVC
HDMI™ plugs and contacts gold plated and moulded
Both sides assembled with ferrite core to dejam signals in the cable (better EMV characteristics)
Full HD - 3D up to 1080p and 4K2K
HEC: HDMI™ Ethernet Channel, ARC: Audio Return Channel

Type of connector connection 1: HDMI-A
Number of poles connection 1: 19
Connection type connection 1: plug
Type of connector connection 2: HDMI-A
Number of poles connection 2: 19
Connection type connection 2: plug

Article no.	Title	Colour	Length m
K7904.1	HighSpeed HDMI™ Cable w.Eth. 3xshie A-A, M-M, 1,0m, black	black	1.0
K7904.2	HighSpeed HDMI™ Cable w.Eth. 3xshie A-A, M-M, 2,0m, black	black	2.0
K7904.3	HighSpeed HDMI™ Cable w.Eth. 3xshie A-A, M-M, 3,0m, black	black	3.0
K7904.5	HighSpeed HDMI™ Cable w.Eth. 3xshie A-A, M-M, 5,0m, black	black	5.0

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.