

CABLE SVGA M/H ALTA CALIDAD CON FERRITA



Double shielded display cable specially capable against outer interference
75 Ohm, double-shielded, with 2 x ferrite cores
With thumb screws, moulded, black
Construction: 3 x coax RGB and 5 x control lines

Type of connector connection 1: HD-D-Sub
Number of poles connection 1: 15
Connection type connection 1: plug
Type of connector connection 2: HD-D-Sub
Number of poles connection 2: 15
Connection type connection 2: jack

TECHNICAL PARAMETERS

Article no.	Title	Colour	Length
CABV2.1,8	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 1,8m, black	black	1.8 m
CABV2.3	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 3,0m, black	black	3.0 m
CABV2.5	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 5,0m, black	black	5.0 m
CABV2.7	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 7,0m, black	black	7.0 m
CABV2.10	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 10,0m, black	black	10.0 m
CABV2.15	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 15,0m, black	black	15.0 m
CABV2.20	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 20,0m, black	black	20.0 m
CABV2.25	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 25,0m, black	black	25.0 m
CABV2.30	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 30,0m, black	black	30.0 m
CABV2.40	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 40,0m, black	black	40.0 m
CABV2.50	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 50,0m, black	black	50.0 m

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.