

Wall-Mounted Distribution Cabinets TWL



Description

Closed sheet steel cabinet with swivel turning handle for profile half-cylinder
 Cable entry at top and bottom via brush terminal
 Colour RAL7035, light grey
 Degree of protection IP40

General data

Model	Wall-mounted distributor
Mounting method	Surface mounted (plaster)
With connecting lugs	Nein
Mounting dimension	96 mm
DIN-compatible	Nein
110-compatible	Nein
LSA	Ja
Material	Steel plate
Degree of protection (IP)	IP40
Colour	Grey

Available variants

Article no.	Title	Type	Module Slots	Max. number of dual cores	Height	Width	Depth	in Pairs	Weight
CAJ300PMLSA	Wall Distribution Cabinet TWL300, W=600 x H=600 x D=240 mm	TWL 300	2 x 18	300	600 mm	600 mm	240 mm	2 x 150	25 kg
CAJ500PMLSA	WM-Distribution Cabinet TWL500, W=600 x H=800 x D=240 mm	TWL 500	2 x 26	500	800 mm	600 mm	240 mm	2 x 250	29 kg
CAJ900PMLSA	WM-Distribution Cabinet TWL900, W=600 x H=1300 x D=240 mm	TWL 900	2 x 46	900	1300 mm	600 mm	240 mm	2 x 450	35 kg
CAJ1350PMLSA	WM-Distribution Cabinet TWL1350, W=800 x H=1300 x D=240 mm	TWL 1350	3 x 46	1350	1300 mm	800 mm	240 mm	3 x 450	40 kg

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.