

Line-Interactive UPS, 600VA/360W



✓ 2x safety outlets

✓ 2-6 ms transfer time (10ms max.)

✓ Compact size

✓ Backup time: 10-12 mins

Abstract

Line-Interactive UPS, 600VA/360W, 12V/7Ah x 1 battery, 2x safety outlets, LED display

Features

- Connection type: 2x safety sockets, 2x RJ11, 1x USB 2.0 type B
- Capacity: 600 VA / 360 W
- Input voltage: 230 VAC
- Voltage range: 162-290 VAC
- Frequency range: 50 Hz (automatic detection)
- Output voltage: 230 VAC \pm 10%
- AC voltage control (battery mode): 10%
- Frequency range (battery mode): 50Hz \pm 1%
- Typical transfer time: 2-6 ms
- Waveform (battery mode): Simulated sine wave
- Battery: 12V / 7Ah x 1
- Typical recharge time: 6-8 hours to restore 90% of the capacity
- Alarm sounds: Battery mode (sounding every 10 seconds), Low battery (sounding every second)
Overload (sounding every 0.5 seconds), fault (continuously sounding)
- Humidity: 0-95% RH at 0 ° C to +40 ° C (non-condensing)
- Noise level: Less than 40 dB
- Boost and Buck AVR for voltage stabilization
- Automatic restart while the AC is recovering
- Dimensions (HxWxD): 142 x 101 x 298 mm
- Weight: 4.35 kg

Product Overview

The Line-Interactive UPS come with a compact size and an excellent microprocessor control, which guarantees high reliability. With an user friendly operation they provide high performance protection for your business and office computer systems against data loss and damage. Features like overload, and overcharge protection, cold start functions and energy saving features, as well as an acoustic alarm system are just a few advantages of the Line-Interactive UPS units.

Product Number Information

Line-Interactive UPS, LED display

S170063 Line-Interactive UPS, 600VA/360W, 12V/7Ah x 1 battery, 2x safety outlets, AVR, RJ-11, LED display

DIGITUS® Line-Interactive UPS, LCD display

S170074 Line-Interactive UPS, 1000VA/600W, 12V/7Ah x 2 battery, 4x safety outlets, AVR, USB, RS232, RJ11/RJ45, LCD display

S170075 Line-Interactive UPS, 1500VA/900W, 12V/9Ah x2 battery, 4x safety outlets, AVR, USB, RS232, RJ-11/45, LCD display

S170076 Line-Interactive UPS, 2000VA/1200W, 12V/9Ah x 2 battery, 4x safety outlets, AVR, USB, RS232, RJ-11/45, LCD display

Product Images

