

Cable de red C14 M/C13 H negro 3x1,00mm.



General data

Plug IEC60320/C14 to jack IEC60320/C13
10 A / 250 V VDE tested

Allgemeine Daten

Number of cores	3
Colour outer sheath	black
With cord switch	False

General data

Spiralized cable	False
------------------	-------

Mechanische Eigenschaften

Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female

Cable sheath

Jacket Material	Polyvinyl chloride (PVC)
-----------------	--------------------------

Kabelmantel

Temperature resistance	0 - 70 °C
------------------------	-----------

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.

Cable de red C14 M/C13 H negro 3x1,00mm.

Electrical characteristics

Protective conductor | True

Elektrische Eigenschaften

Nominal voltage | 250 V

Standards, approvals, certifications

Oil resistant (acc. EN 60811-2-1) | False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Leiternennquerschnitt	Außendurchmesser ca.
EK503.0,5	Extension Cable C14 180° - C13 180°, Black, 0.5 m, 3 x 0.75 mm ²	black	0.5 m	0,75 mm ²	6,8 mm
EK503.1	Extension Cable C14 180° - C13 180°, Black, 1.0 m, 3 x 0.75 mm ²	black	1.0 m	0,75 mm ²	6,8 mm
EK503.2	Extension Cable C14 180° - C13 180°, Black, 2.0 m, 3 x 0.75 mm ²	black	2.0 m	0,75 mm ²	6,8 mm
EK503.3	Extension Cable C14 180° - C13 180°, Black, 3.0 m, 3 x 1.00 mm ²	black	3.0 m	1,00 mm ²	7,1 mm
EK503.5	Extension Cable C14 180° - C13 180°, Black, 5.0 m, 3 x 1.00 mm ²	black	5.0 m	1,00 mm ²	7,1 mm

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.