

# Latiguillo ST/ST DUPLEX 62.5/125 OM1 MM



## General data

Fiber jumper are well defined components in international standard of structured cabling ISO/IEC11801. Due to many different network protocols created in the last 25 years , also a wide range of connectors had been developed. Some of them are still important today: LC, SC, E2000®, MPO/MTP.

Fiber jumper (patchcord) are defined as shortest connection between passive interface and active deviceport, regarding structured cabling standard. Rating of performance, known as category, as well as performance of total transmission channel, known as link class, Similar descriptions for patchcords: Connection cable, drop cable, adapter cable, interconnecting cord, Jumper

## fiber optic patch cables

Tension relief reinforced with aramid yarn

Halogen-free and flame-retardant sheath according to IEC-60754-2, IEC-60332-1 and IEC-61034

fiber optic connectors meet the minimum quality class Grade B/2 according to IEC-61753-1 for singlemode and Grade A/1 for multimode according to IEC 61753-122-2 (UPC cut)

100% tested and with individual measurement report

## Allgemeine Daten

Insertion loss 850nm	< 0.3 dB
Colour outer sheath	orange
Halogen free	acc. IEC60754-1
APC-version	False
Number of fibres	2
Material outer sheath	LSZH
Cable type	I-V(ZN) H
Anti-kink sleeve	put-on

*Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.*

# Latiguillo ST/ST DUPLEX 62.5/125 OM1 MM

Category	OM1
----------	-----

## Mechanische Eigenschaften

Min. Bending radius (Dynamic)	20xOD
Cable Ø	3.0 mm
Max. Tension	160 N
Min. Bending radius (Static)	10xOD

## Kabelaufbau

Type of connector connection 2	ST
Type of connector connection 1	ST
Cable Construction	Duplex
Fibre type	Multi mode 62.5/125

## Kabelmantel

Flame retardant	According to EN 50265-2-1
Halogen free (according to EN 50267-2-3)	True
Low smoke	acc. IEC61034-1

## Umgebungsbedingungen

Storage Temperature	-20 - 85 °C
Operating Temperature	-20 - 75 °C

## Übertragungstechnische Eigenschaften

Quality class multimode	A/1 according to IEC-61753-222-2
-------------------------	----------------------------------

## Normen, Zulassungen, Zertifizierungen

Connector Conform to Standard	IEC 61754-2
Cable Conform to Standard	IEC 60793-2

## Drawings

