



Customer No: _____

△*NOTE: ALL relevant materials are complied with ROHS directive

2057	
P1	P2
1	1 BROWN
2	3 RED
3	2 ORANGE
4	5 YELLOW
5	4 GREEN
6	20 BLUE
8	
7	7 PURPLE
20	6 BLACK
	8
SHIELD	SHIELD

No.	DESCRIPTION	Q'TY	Supplier
6	Jumper Wire UL1061/28#/1C x 28mm ID0.0.9 DRAWING NO.EH002801C-024	1	M304
	BLACK PVC TUBE ϕ 3.0*30mm	1	M304
	ALUMINUM FOIL 33*110mm	1	M309
	MOLDED PE COLOR TRANSPARENT		M280
	MOLDED PVC BEIGE		M304
5	Jumper Wire UL1061/28#/1C x 28mm ID0.0.9 DRAWING NO.EH002801C-024	1	M304
	BLACK PVC TUBE ϕ 3.0*30mm	1	M304
	ALUMINUM FOIL 33*110mm	1	M309
	MOLDED PE COLOR TRANSPARENT		M280
4	NON-UL 8C 28AWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 5.0mm, JACKET BEIGE, DRAWING No. EMAL2808C-045	Lmm	M304
	MOLDED THUMBSCREW #4-40, LENGTH 46.5mm, BEIGE	4	M95
2	DB25 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M277
1	DB25 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	M277

APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm			
CHECKED	HU				
DRAWING	ZHU				
DATE	05/JULY/19	ITEM NO.	DNC-25MF-XXB & DNC-25MF-XXB-MF	UNIT:mm	