

Terminal horquilla aislado 1,0-2,5 azul en Y

Ref.: EF-25043-A



| Art. | mm ² /AWG | d | B | L | F | D | E | |
|---------------|----------------------|------|------|------|------|-----|------|----------|
| ■ EF-25032-A | 1.50-2.50 / 16-14 | 3.2 | 5.7 | 22.5 | 8.5 | 4.5 | 11.0 | 100/1000 |
| ■ EF-25037-A | | 3.7 | 5.7 | 22.5 | 6.5 | | | |
| ■ EF-25037-1A | | 3.7 | 6.2 | 22.5 | 6.5 | | | |
| ■ EF-25043-A | | 4.3 | 6.4 | 22.5 | 6.5 | | | |
| ■ EF-25043-1A | | 4.3 | 7.2 | 22.5 | 6.5 | | | |
| ■ EF-25053-A | | 5.3 | 8.0 | 22.5 | 6.5 | | | |
| ■ EF-25064-A | | 6.4 | 10.8 | 23.5 | 7.6 | | | |
| ■ EF-25064-1A | | 6.4 | 9.3 | 23.0 | 13.7 | | | |
| ■ EF-25084-A | | 8.4 | 13.5 | 28.5 | 21.0 | | | |
| ■ EF-25105-A | | 10.5 | 15.0 | 30.5 | 13.9 | | | |
| ■ EF-55032-A | 4.00-6.00 / 12-10 | 3.2 | 7.3 | 26.7 | 7.1 | 6.6 | 14.0 | 50/500 |
| ■ EF-55037-A | | 3.7 | 6.3 | 26.7 | 7.1 | | | |
| ■ EF-55037-1A | | 3.7 | 8.1 | 26.7 | 7.1 | | | |
| ■ EF-55043-A | | 4.3 | 6.3 | 26.7 | 7.4 | | | |
| ■ EF-55043-1A | | 4.3 | 8.2 | 26.7 | 7.5 | | | |
| ■ EF-55053-A | | 5.3 | 9.0 | 26.7 | 8.0 | | | |
| ■ EF-55064-A | | 6.4 | 12.0 | 30.3 | 9.9 | | | |
| ■ EF-55064-1A | | 6.4 | 9.0 | 30.7 | 26.2 | | | |
| ■ EF-55084-A | | 8.4 | 13.5 | 32.6 | 25.4 | | | |
| ■ EF-55105-A | | 10.5 | 15.0 | 40.0 | 13.4 | | | |

Ideal Technology tiene una política de mejora continua. Las especificaciones están sujetas a cambios sin previo aviso.