


Terminal redondo preaislado 0,5-1,5 /rojo /M4

Ref.: EF-15043

								105° / 600 V / PA / Cu	
									Medidas en mm.
Art.	mm²/AWG	d	B	L	F	D	E		
 EF-05022	0.14-0.34 / 26-22	2.2	6.0	18.6	8.0	2.3	8.0	100/1000	
 EF-05027		2.7	6.0	18.6	8.0				
 EF-05032		3.2	6.0	18.6	8.0				
 EF-05037		3.7	8.0	19.0	8.0				
 EF-05043		4.3	8.6	19.3	8.0				
 EF-05053		6.3	8.0	20.0	8.0				
 EF-15032	0.60-1.60 / 20-18	3.2	6.6	17.6	4.3	4.1	10.6	100/1000	
 EF-15037		3.7	6.6	17.6	4.3				
 EF-15037-1		3.7	8.8	20.4	8.8				
 EF-15043		4.3	8.8	20.4	8.8				
 EF-15043-1		4.3	8.0	21.8	7.3				
 EF-15053		6.3	8.0	21.8	7.3				
 EF-15064		8.4	11.8	27.6	11.2				
 EF-15084		8.4	11.8	27.6	11.2				
 EF-15105		10.6	13.7	31.6	14.2				
 EF-15105-1		10.6	18.6	30.6	12.3				
 EF-15130		13.0	19.8	38.4	16.0				
 EF-25032	1.60-2.60 / 16-14	3.2	8.8	20.8	8.3	4.6	11.0	100/1000	
 EF-25032-1		3.2	8.6	23.0	7.8				
 EF-25037		3.7	8.8	20.8	8.3				
 EF-25037-1		3.7	8.6	23.0	7.8				
 EF-25043		4.3	8.8	20.8	8.3				
 EF-25043-1		4.3	8.6	23.0	7.8				
 EF-25053		6.3	8.6	23.0	7.8				
 EF-25053-1		6.3	9.6	22.9	7.3				
 EF-25064		8.4	12.0	28.0	11.0				
 EF-25084		8.4	12.0	28.0	11.0				
 EF-25105		10.6	13.8	31.7	13.9				
 EF-25130		13.0	19.2	38.4	16.0				
 EF-55032	4.00-8.00 / 12-10	3.2	9.6	26.7	8.0	8.8	14.0	60/600	
 EF-55037		3.7	9.6	26.7	8.0				
 EF-55043		4.3	7.4	26.7	8.0				
 EF-55043-1		4.3	9.6	26.7	8.0				
 EF-55053		6.3	9.6	26.7	8.0				
 EF-55053-1		6.3	7.4	26.7	26.1				
 EF-55064		8.4	12.0	32.7	12.7				
 EF-55084		8.4	16.0	34.9	13.4				
 EF-55105		10.6	16.0	34.9	13.4				
 EF-55130		13.0	19.2	39.6	16.0				

Ideal Technology tiene una política de mejora continua. Las especificaciones están sujetas a cambios sin previo aviso.