

DATASHEET

Power Cable Euro - C7 180°, Black, 5.0 m, 2 x 0.75 mm²



General data

2.5 A / 250 V VDE tested

Suitable for Europe, except of UK, Ireland, Malta, Cyprus

Allgemeine Daten

Colour outer sheath	black
With cord switch	False
Jacket Material	Polyvinyl chloride (PVC)
Number of cores	2

General data

Spiralized cable	False
Halogen free	False

Mechanische Eigenschaften

Connection 1	EURO plug (CEE 7/16)
Connection 2	C7 plug female 180°

This datasheet was created automatically on 25-09-2024 . Technical changes reserved.



DATASHEET

Power Cable Euro - C7 180°, Black, 5.0 m, 2 x 0.75 mm²

Cable sheath

Oil resistant (according to EN 60811-404)	False
---	-------

Kabelmantel

Temperature resistance	0 - 70 °C
------------------------	-----------

Electrical characteristics

Protective conductor	False
----------------------	-------

Elektrische Eigenschaften

Nominal voltage	250 V
-----------------	-------

Standards, approvals, certifications

Oil resistant (acc. EN 60811-2-1)	False
-----------------------------------	-------

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	With protective conductor	Leiternennquerschnitt	Außendurchmesser ca.
EK502.1V2	Power Cable Euro - C7 180°, Black, 1.0 m, 2 x 0.75 mm ²	black	1.0 m	-	False	0,75 mm ²	3,5 x 5,7 mm
EK502.2V2	Power Cable Euro - C7 180°, Black, 2.0 m, 2 x 0.75 mm ²	black	2.0 m	2.5 A	False	0,75 mm ²	3,5 x 5,7 mm
EK502.3V2	Power Cable Euro - C7 180°, Black, 3.0 m, 2 x 0.75 mm ²	black	3.0 m	-	False	0,75 mm ²	3,5 x 5,7 mm
EK502.5V2	Power Cable Euro - C7 180°, Black, 5.0 m, 2 x 0.75 mm ²	black	5.0 m	-	False	0,75 mm ²	3,5 x 5,7 mm

This datasheet was created automatically on 25-09-2024 . Technical changes reserved.

