

DATASHEET

Power Cable CEE7/7 90° - C13 180°, Black 3.0 m, 3 x 1.00 mm²



General data

10 A / 250 V VDE tested

Suitable for Germany, Belgium, France and further

Technical properties

Colour outer sheath	black
Connection 1	Socket outlet with protective contact, right-angled
Connection 2	Cold device plug straight, female
Halogen free	No
Jacket material	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Temperature resistance	3 - 70 °C
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Nominal cross Length section conductor	Outer diameter approx.
--------	-------------	---------------------------	--	------------------------------

DATASHEET

Power Cable CEE7/7 90° - C13 180°, Black 3.0 m, 3 x 1.00 mm²

EK504.0,5V2	Power Cable CEE7/7 90° - C13 180° Black 0.5 m, 3 x 0.75 mm ²	black	0.5 m	0.75 mm ²	6.5 mm
EK504.0,75V2	Power Cable CEE7/7 90° - C13 180° Black 0.75 m, 3 x 0.75 mm ²	black	0.75 m	0.75 mm ²	6.5 mm
EK504.1V2	Power Cable CEE7/7 90° - C13 180° Black 1,0 m, 3 x 0.75 mm ²	black	1.0 m	0.75 mm ²	6.5 mm
EK504.2V2	Power Cable CEE7/7 90° - C13 180°, Black 2.0 m, 3 x 0.75 mm ²	black	2.0 m	0.75 mm ²	6.5 mm
EK504.3V2	Power Cable CEE7/7 90° - C13 180°, Black 3.0 m, 3 x 1.00 mm ²	black	3.0 m	1.00 mm ²	6.8 mm
EK504.5V2	Power Cable CEE7/7 90° - C13 180°, Black 5.0 m, 3 x 1.00 mm ²	black	5.0 m	1.00 mm ²	6.8 mm

Drawings

