

DATASHEET

Power Cable CEE7/7 90° - Open End WES, 3.0 m, 3 x 1.00 mm²



General data

16 A / 250 V VDE tested
Open End assembled with wire end sleeves
Wire end sleeves for 1.8 m: L = 6 mm, Ø 1.7 mm, yellow insulator
Wire end sleeves for 3 + 5 m: L = 8 mm, Ø 1.7 mm, red insulator
Cable colour black
Suitable for Germany, Belgium, France and further

Technical properties

Colour outer sheath	black
Connection 1	Socket outlet with protective contact, right-angled
Connection 2	Cable end sleeve
Halogen free	No
Jacket material	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Temperature resistance	3 - 70 °C
With cord switch	False

Ideal Technology tiene una política de mejora continua. Las especificaciones están sujetas a cambios sin previo aviso.

DATASHEET

Power Cable CEE7/7 90° - Open End WES, 3.0 m, 3 x 1.00 mm²

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK504AE.1,8	Power Cable CEE7/7 90° - Open End WES, 1.8 m, 3 x 0.75 mm ²	black	1.8 m	True	0.75 mm ²	6.8 mm
EK504AE.3	Power Cable CEE7/7 90° - Open End WES, 3.0 m, 3 x 1.00 mm ²	black	3.0 m	True	1.00 mm ²	7.1 mm
EK504AE.5	Power Cable CEE7/7 90° - Open End WES, 5.0 m, 3 x 1.00 mm ²	black	5.0 m	True	1.00 mm ²	7.1 mm

Ideal Technology tiene una política de mejora continua. Las especificaciones están sujetas a cambios sin previo aviso.