

DATASHEET

Power Cable CEE7/7 90° - C13 180°, White, 3.0 m, 3 x 1.00 mm²



General data

Coloured power cords for clearly assignment of device - cable - outlet

No time-intensive search or tracing of cables

CEE7/3 Plug CEE7/7 90° - C13 180° (IEC jack)

Cable H05VV-F 3G 0.75 qmm

10 A / 250 V VDE tested

The coloured power cords enable an instant visual assignment of devices and the corresponding power cord.

Technical properties

Colour outer sheath	white
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Cold device plug straight, female
Halogen free	False
Jacket material	Polyvinylchlorid (PVC)
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Protective conductor	True
Spiralized cable	False
Temperature resistance	0 70 °C
With cord switch	False

Available variants

This datasheet was created automatically on 18-02-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180°, White, 3.0 m, 3 x 1.00 mm²

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK588WS.1,8V2	Power Cable CEE7/7 90° - C13 180°, White, 1.8 m, 3 x 0.75 mm ²	white	IP20	1.8 m	10 A	250 V	Ja	0.75 mm ²	6.5 mm
EK588WS.3V2	Power Cable CEE7/7 90° - C13 180°, White, 3.0 m, 3 x 1.00 mm ²	white	IP20	3.0 m	10 A	250 V	Ja	1.0 mm ²	7.0 mm

This datasheet was created automatically on 18-02-2026 . Technical changes reserved.

