

DATASHEET

Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010



Class E



General data

Cat.6 (250 MHz) according to ISO/IEC 11801 and EN50173
 40° outlet, 8-pole IDC terminals
 Fully shielded diecast housing
 Labelling field with transparent cover
 For installation in ducts and underfloor systems
 Central plate according to DIN49075
 Central plate 50 x 50 mm, including cover plate 80 x 80 mm
 Design capable, compatible with all common switch programmes

Technical properties

Category

6

This datasheet was created automatically on 04-02-2026 . Technical changes reserved.



DATASHEET

Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010

Centre plate	True
Colour coding	True
Connection type	LSA
Cover frame	True
Degree of protection	IP20
Design suitable	True
Duct installation	True
Floor box/sub-floor mounted	True
Flush mounted (plaster)	True
Mechanical coding	False
Mounting method shielding connection	screw/lock
Outlet direction	Inclined
POE Standard	POE+
RAL number	9010
Separate earthing connection	True
Separate strain relief	True
Shielded buses	True
Shielded housing	True
Suitable for number of connectors	2
Surface mounting	False
Tape width	250 MHz
Temperature Range (Operation)	-10 - 60 °C
Temperature Range (Storage)	-40 - 70 °C
Terminal resistor	False
Transmission	2.5 Gbit
Type of connector	RJ45 2x8(8)
Type of fastening	Screwing
With buses/couplings	True
With dust cover	True
With label space	True

Available variants

ArtNr.	Bezeichnung	Assembly arrangement	Depth of device	Flush-mounted installation	Height of device	Supply line for installation cable	Width of device	With terminal resistor	Colour
--------	-------------	----------------------	-----------------	----------------------------	------------------	------------------------------------	-----------------	------------------------	--------

This datasheet was created automatically on 04-02-2026 . Technical changes reserved.



Calle del Horno, 84-85,
Polígono Industrial "Villa de Azafía"
45230 Numancia de la Sagra (TOLEDO)

info@sunprored.es
comercial@sunprored.es

915 00 79 63

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION



DATASHEET

Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010

ET-25211.1V1	Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010	Basic element with central cover plate	40.95 mm	True	50 mm	vertical	50 mm	False	white
ET-25211.2V1	Data outlet Cat.6 250MHz, right/left, Flush, 2xRJ45, RAL9010	Basic element with central cover plate	40.95 mm	True	50 mm	Left/right	50 mm	False	white

This datasheet was created automatically on 04-02-2026 . Technical changes reserved.

