

DATASHEET

RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 5m



General data

RJ45 flat patch cable Cat.6A U/FTP PVC

The Cat.6A (TIA) patch cable has gold-plated contacts and meets the requirements for 10Gbit Ethernet.

Technical product features

- Cat.6A (TIA)
- U/FTP cable with AWG30/7
- Sheath material made of polyvinyl chloride (PVC)
- Plug connection: RJ45 to RJ45
- With locking lever protection
- Has gold-plated contacts

The sheath of the shielded patch cable is made of polyvinyl chloride (PVC) material. In addition, the cable offers the option of power supply via PoE+ according to IEEE802.3at and PoE according to IEEE802.3af.

This datasheet was created automatically on 16-12-2024 . Technical changes reserved.



Calle del Horno, 85, en el Polígono Industrial
"Villa de Azaña", 45230 Numancia de la
Sagra (TOLEDO)

info@sunprored.es
comercial@sunprored.es

915 00 79 63

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION



DATASHEET

RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 5m

The assignment of the particularly short RJ45 plugs is 1:1 and follows TIA/EIA 568B . Suitable for the temperature range -20 - 55 °C.

The Ethernet cable has a copper conductor material and is ideal for applications in structured building cabling, industrial Ethernet and data centers. This achieves a bandwidth of 500 MHz.

Allgemeine Daten

Suitable for degree of protection (IP)	IP20
AWG-size	30/7
Length imprint	False
Jacket Material	TPE/LSZH

General data

Connector type	RJ45 short version
Colour outer sheath	black
Pin assignment	1:1
Locking lever	True
Fire retardant version	True
Model	Shielded
Contacts	Gold plated
Allocation	acc. TIA/EIA 568B
Cable type	U/FTP
Area of Application	Industrial Ethernet
Anti-kink sleeve	plugged in
Halogen free	True
Category	6A (TIA)
Colour anti-kink sleeve	black

Mechanical characteristics

Conductive shield	Selected shield contact
Bending radius	>16 mm
Mating cycles	2000

Cable construction

Conductor Material	Copper
--------------------	--------

Kabelaufbau

Type of connector connection 2	RJ45 8(8)
--------------------------------	-----------

This datasheet was created automatically on 16-12-2024 . Technical changes reserved.



DATASHEET

RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 5m

Type of connector connection 1	RJ45 8(8)
Cable construction	4x2

Cable sheath

Low smoke	True
Oil resistant (according to EN 60811-404)	False
Outer diameter of the cable	4.0 mm
Silicone-free	True

Kabelmantel

Printing	Cat.6A Patchcord ULTRAFLEX U/FTP TPE 10G www.efb-elektronik.de
----------	---

Environmental conditions

Temperature range	-20 - 75 °C
-------------------	-------------

Electrical characteristics

Loop resistance	752 Ω/km
Impedance	100 ±15 Ω
Conductor resistance DC	376 Ω/km
Resistance unbalance	< 4 %
Contact Resistance	< 20 mΩ
POE class	PoE+ acc. to IEEE802.3at
Operating-/ tempering voltage	max. 50 V DC
Current Rating	max. 1 A
NVP value	76 %
Insulation Resistance	100 MΩ

Elektrische Eigenschaften

Test voltage	1000 (V DC, 1min) core/core und core/screen
--------------	---

Übertragungstechnische Eigenschaften

Bandwidth	500MHz
-----------	--------

Standards, approvals, certifications

Cabling standard	EN50173
------------------	---------

This datasheet was created automatically on 16-12-2024 . Technical changes reserved.



DATASHEET


RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 5m

Oil resistant (acc. EN 60811-2-1)	False
Connector	IEC 60603-7-51

Available variants

ArtNr.	Bezeichnung	Length Längentoleranz
K5547SW.0,15	RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 0,15m	0.15 m $\pm 5\%$
K5547SW.0,25	RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 0,25m	0.25 m $\pm 5\%$
K5547SW.0,5	RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 0,5m	0.5 m $\pm 5\%$
K5547SW.1	RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 1m	1.0 m $\pm 5\%$
K5547SW.1,5	RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 1,5m	1.5 m $\pm 5\%$
K5547SW.2	RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 2m	2.0 m $\pm 5\%$
K5547SW.3	RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 3m	3.0 m $\pm 5\%$
K5547SW.5	RJ45 Patch Cord Cat.6A U/FTP TPE4mm ultraflex black 5m	5.0 m $\pm 5\%$

Drawings



This datasheet was created automatically on 16-12-2024 . Technical changes reserved.