

Serie Kryptos Serie

Digital interactive



The **KRYPTOS UPS** stands out for offering complete protection in a compact and comfortable format. With 6 Schuko sockets (3 of them Surge Protec) it offers a high level of autonomy in the event of power failures and protects the connected equipment against overvoltages, overloads or short circuits.

Data Sheet

Reference	PH 9478
Power	800 VA / 480 W
Input	
Rated Voltage	220 / 230 / 240 Vac
Voltage Range	180 - 270 Vac
Frequency	50 Hz / 60 Hz (Auto detection)
Salida	
Voltage Regulation (Bat.)	220 – 240 Vac
Frequency (Bat.)	50 Hz / 60 Hz $\pm$ 1%
Waveform (Bat.)	Modified sinusoidal
Transfer time	2 - 6 ms
Overload protection	Circuit breaker or internal protection fuse
Battery	
Quantity / Tipe / n°	1x 12V/ 5 Ah
Charging time (90%)	8 h
Indicators	
Led	LCD
Warning	Battery On / Battery Low / Overload / Fault
Characteristics	
Dimensions (WxHxD)	305 x 158.5 x 95
Weight (Kg)	2.9
Operating humidity	0 – 90 % without condensation
Operating temperature	0 - 40°C
Specifications subject to change without notice. PHASAK® copyrights.	

