


Terminal horquilla preaislado 0,5-1,5 rojo

Ref.: PVC-15037-A

Horquillas

75° / 600 V / PVC / Cu								
 								
Art.	mm²/AWG	d	B	L	F	D	E	Medidas en mm.
PVC-15032-A	0.60-1.60 / 20-18	3.2	6.7	22.0	7.2	4.3	10.3	100/1000
PVC-15037-A		3.7	6.7	22.0	7.2			
PVC-15037-1A		3.7	8.2	22.0	7.2			
PVC-15043-A		4.3	8.4	22.0	7.2			
PVC-15043-1A		4.3	7.2	22.0	7.2			
PVC-15053-A		6.3	8.0	22.0	8.6			
PVC-15064-A		8.4	10.8	23.0	8.0			
PVC-15064-1A		8.4	8.3	23.0	8.0			
PVC-15084-A		8.4	13.6	28.0	10.6			
PVC-15105-A		10.6	16.0	20.6	11.0			
PVC-25032-A	1.60-2.60 / 18-14	3.2	6.7	22.6	8.6	4.9	11.0	100/1000
PVC-25037-A		3.7	6.7	22.6	8.6			
PVC-25037-1A		3.7	8.2	22.6	8.6			
PVC-25043-A		4.3	8.4	22.6	8.6			
PVC-25043-1A		4.3	7.2	22.6	8.6			
PVC-25053-A		6.3	8.0	22.6	8.6			
PVC-25064-A		8.4	10.8	23.6	7.7			
PVC-25064-1A		8.4	8.3	23.6	7.7			
PVC-25084-A		8.4	13.8	28.6	8.0			
PVC-35037-A	2.60-4.00 / 14-12	3.7	7.3	28.0	8.3	8.1	14.0	100/1000
PVC-35043-A		4.3	8.0	26.0	8.3			
PVC-35053-A		6.3	8.0	26.0	8.7			
PVC-55032-A	4.00-8.00 / 12-10	3.2	7.3	28.7	8.7	8.7	14.0	60/600
PVC-55037-A		3.7	8.3	28.7	7.1			
PVC-55037-1A		3.7	8.1	28.7	7.1			
PVC-55043-A		4.3	8.3	28.7	7.4			
PVC-55043-1A		4.3	8.2	28.7	7.6			
PVC-55053-A		6.3	9.0	28.7	8.0			
PVC-55064-A		8.4	12.0	30.7	8.90			
PVC-55064-1A		8.4	8.0	30.7	8.90			
PVC-55084-A		8.4	13.6	32.6	12.0			

Ideal Technology tiene una política de mejora continua. Las especificaciones están sujetas a cambios sin previo aviso.