




Terminal tubular cobre sin soldadura

Ref.: TD-16-8



Material: Cobre
Acabado: Estañado

Ref.	Sección cable mm ²	Dimensiones mm.			Bolsa		Ref.	Sección cable mm ²	Dimensiones mm.			Bolsa		
		Ø D	B	L					Ø D	B	L			
TD-15-4	1.5	4.3	8.0	17.0	100	3.000	TD-50-6	50.0	6.4	18.0	43.0	50	2	
TD-15-5		5.3	8.0	17.0			TD-50-8		8.4	18.0	43.0			
TD-25-4	2.5	4.3	8.0	18.0	100	2.000	TD-50-10	10.5	18.0	43.0	50	1		
TD-25-5		5.3	8.0	20.0			TD-50-12		13.0	18.0			51.5	
TD-25-6		6.4	9.0	20.0			TD-50-14		15.0	25.0			55.5	
TD-4-4	4.0	4.3	10.0	21.0	100	2.000	TD-50-16	17.0	26.0	59.5	50	1		
TD-4-5		5.3	10.0	21.0			TD-70-6		70.0	6.4			21.8	50.0
TD-4-6		6.4	10.0	21.0			TD-70-8		8.4	21.8			50.0	
TD-6-4	6.0	4.3	10.0	23.0	100	1.000	TD-70-10	10.5	21.8	50.0	50	1		
TD-6-5		5.3	10.0	26.0			TD-70-12		13.0	21.8			50.0	
TD-6-6		6.4	10.0	26.0			TD-70-14		15.0	21.8			59.0	
TD-6-8	8.4	12.0	27.5	100	1.000	TD-70-16	17.0	26.0	63.0	50	1			
TD-6-10		10.5	16.0			34.0		TD-95-5	95.0			5.3	25.0	57.0
TD-10-5		10.0	5.3			12.0		26.5	100			1.000	TD-95-6	6.4
TD-10-6	6.4		12.0	26.5	TD-95-8	8.4	25.0	57.0						
TD-10-8	10.5	8.4	12.0	26.5	800	500	TD-95-10	10.5	25.0	57.0	50	1		
TD-10-10		10.5	18.0	35.5			TD-95-12		13.0	25.0			57.0	
TD-10-12		13.0	18.5	39.5			TD-95-14		15.0	25.0			65.5	
TD-16-4	16.0	4.3	12.4	31.0	100	800	TD-95-16	17.0	27.0	69.5	50	1		
TD-16-5		5.3	12.4	31.0			TD-95-20		21.0	29.5			77.5	
TD-16-6		6.4	12.4	31.0			TD-120-8		120.0	8.4			28.0	60.0
TD-16-8	8.4	12.4	31.0	100	800	TD-120-10	10.5	28.0	60.0	25	1			
TD-16-10		10.5	15.0			33.0		TD-120-12	13.0			28.0	60.0	
TD-16-12		13.0	20.0			42.5		TD-120-14	15.0			28.0	66.0	
TD-25-5	25.0	5.3	14.0	32.0	100	500	TD-120-16	17.0	28.0	66.0	25	1		
TD-25-6		6.4	14.0	32.0			TD-150-10		150.0	10.5			30.5	69.0
TD-25-8		8.4	18.0	34.0			TD-150-12		13.0	30.5			69.0	
TD-25-10	10.5	18.0	34.0	100	400	TD-150-14	15.0	30.5	69.0	200	1			
TD-25-12		13.0	20.0			45.0		TD-150-16	17.0			30.5	69.0	
TD-35-6		35.0	6.4			16.0		38.0	100			300	TD-150-20	21.0
TD-35-8	8.4		16.0	38.0										
TD-35-10	10.5		17.5	40.5										
TD-35-12	13.0	18.0	47.5	100	200									

2-76

Ideal Technology tiene una política de mejora continua. Las especificaciones están sujetas a cambios sin previo aviso.