

Puntera hueca aislada 0.75mm. l=8mm. azul

Ref.: TE0.75

Art.		Art. (DIN 46228/4)	mm²/AWG	L	F	Medidas en mm.
						
TE-0.14 *		---	0.14 / 26	10.0	6.0	100
TE-0.14-L		---		12.0	8.0	
TE-0.25 *		PD-0.25	0.25 / 24	10.0	6.0	100
TE-0.25-L		PD-0.25-L		12.0	8.0	
TE-0.34 *		PD-0.34	0.34 / 22	10.0	6.0	100
TE-0.34-L		PD-0.34-L		12.0	8.0	
TE-0.50-K		PD-0.50-K	0.50 / 20	12.0	6.0	100
TE-0.50 *		PD-0.50		14.0	8.0	
TE-0.50-HL		PD-0.50-HL		16.0	10.0	
TE-0.75-K		PD-0.75-K	0.75 / 18	12.0	6.0	100
TE-0.75 *		PD-0.75		14.0	8.0	
TE-0.75-HL		PD-0.75-HL		16.0	10.0	
TE-0.75-L		PD-0.75-L		18.0	12.0	
TE-1.00-K		PD-1.00-K	1.00 / 17	12.0	6.0	100
TE-1.00 *		PD-1.00		14.0	8.0	
TE-1.00-HL		PD-1.00-HL		16.0	10.0	
TE-1.00-L		PD-1.00-L		18.0	12.0	
TE-1.50-K		PD-1.50-K	1.50 / 16	12.0	6.0	100
TE-1.50 *		PD-1.50		14.0	8.0	
TE-1.50-HL		PD-1.50-HL		16.0	10.0	
TE-1.50-HLS		PD-1.50-HLS		18.0	12.0	
TE-1.50-L		PD-1.50-L		24.0	18.0	
TE-2.50 *		PD-2.50	2.50 / 14	14.0	8.0	100
TE-2.50-HLS		PD-2.50-HLS		16.0	10.0	
TE-2.50-HL		PD-2.50-HL		18.0	12.0	
TE-2.50-L		PD-2.50-L		24.0	18.0	
TE-4.00 *		PD-4.00	4.00 / 12	17.0	10.0	100
TE-4.00-HL		PD-4.00-HL		20.0	12.0	
TE-4.00-L		PD-4.00-L		26.0	18.0	
TE-6.00 *		PD-6.00	6.00 / 10	20.0	12.0	100
TE-6.00-L		PD-6.00-L		26.0	18.0	
TE-10.00 *		PD-10.00	10.00 / 8	22.0	12.0	100
TE-10.00-L		PD-10.00-L		26.0	18.0	

Ideal Technology tiene una política de mejora continua. Las especificaciones están sujetas a cambios sin previo aviso.